### **MAGEWELL**

# **Ultra Stream HDMI Technical Specifications**

Copyright (c) 2011-2019 Magewell Electronics Co., Ltd. All rights reserved.

Specifications are based on current hardware, firmware and software revisions, and are subject to change without notice.

HDMI, the HDMI logo and High-Definition Multimedia interface are trademarks or registered trademarks of HDMI Licensing LLC.

Windows is trademark or registered trademark of Microsoft Corporation.

Android is trademark or registered trademark of Google Corporation.

iOS is trademark or registered trademark of Apple Corporation.

Revised 09/07/2019

### **Supported Mobile Clients**

- Android
  - Android 5.0 and above
- iOS
  - o iOS 9.0 and above
- iPhone
  - iPhone 5s
  - iPhone SE
  - iPhone 6 / iPhone 6s / iPhone 6 Plus / iPhone 6s Plus
  - o iPhone 7 / iPhone 7 Plus
  - iPhone 8 / iPhone 8 Plus
  - iPhone X
- iPod Touch
  - iPod Touch 5
  - iPod Touch 6

# Supported Web Browser

- Microsoft Internet Explorer 11
- Microsoft Edge
- Mozilla Firefox version 61 and above
- Google Chrome version 49 and above
- Apple Safari 11.1 and above
- Opera 55.0.2994.44 and above

# Input Interfaces

- HDMI
  - HDMI 1.4a
- 3.5mm audio jack
  - Microphone interface

# **Output Interfaces**

- HDMI
  - HDMI loop-through
- USB
  - o USB 2.0
- 3.5mm audio jack
  - Headphone interface

#### **Network Interfaces**

• Wired Ethernet

- 10/100/1000Mbps Ethernet
- Wi-Fi
  - IEEE 802.11 a/b/g/n/ac
- USB
  - USB 3G/4G Modem (not included)

#### **Bluetooth**

• Bluetooth 4.0 BLE

#### **HDMI Specific Features**

- Support for up to 4096x2160 4:4:4/4:2:2 30fps or 4096x2160 4:2:0 60fps input and loopthrough signals
- Support for 8/10/12-bit color depths
- Support for 60p, 60i, 50p, 50i, 30p, 25p signal formats

### **Analog Audio Features**

- Extraction of stereo embedded HDMI audio for recording and output via 3.5mm stereo mini-jack Line Out
- Recording and streaming analog audio via 3.5 mm microphone interface

### **Streaming Features**

- Support for live streaming using RTMP protocol to software including Flash Media Server, Wowza, Red5 and Nginx server
- Streaming to Facebook, Twitch and YouTube platforms
- Support for streaming to 2 servers simultaneously

### Recording Features (to USB Flash Drive)

- Support for H.264/HEVC (video) and AAC High Quality (audio) encoding
- Supports recording at input signal resolution up to 2048x1080
- Support for 1920x1080, 1600x1200, 1440x1080, 1440x900, 1280x1024, 1280x960, 1280x800, 1280x720, 1200x900, 1024x768, 960x540, 800x600, 768x576, 720x576, 720x480, 640x480, 640x360, 480x360 resolutions
- Support for 60fps, 50fps, 30fps, 25fps, 24fps, 15fps frame rates
- Support for recording as MP4 files
- USB Flash Drive file system format: FAT32, NTFS, exFAT, VFAT

# **Recording Features (to Mobile Device)**

- Support for recording at up to 1280x720, 30fps
- · Support for recording as MP4 files
- Take still image snapshots during recording
- Save recording files and screenshots to system album
- Input signal previewing
- Timer recording: 15s, 30s, 1min, 2min, 5min

# **Remote Control Features in App**

- Remotely control recording and streaming
- Remotely check device status
- Support for setting volume, network, recording and live streaming parameters
- Support for checking and safely updating device firmware (can also reset to factory firmware version)
- Simultaneous main stream and sub stream encoding with customizable parameters
- The bitrate for main stream is up to 8 Mbps while for sub stream is 1 Mbps
- In-app online help
- Support for multiple users log-in simultaneously
- Support for device configuration using Web UI

#### **LED Indicator**

- Indicates the state of the input signal, Ethernet Network, Wi-Fi, USB flash drive
- Indicates the working state of the device: startup, recording, streaming, update

#### **Form Factor**

• 94.20mm x 94.20mm x 28.50mm

#### **Accessories**

• AC adapter

# **Power Supply and Consumption**

- Power port5V/2A
- Max power consumption: ~6.0 W

# **Working Environment**

Operating temperature: 0 to 40 deg C
Storage temperature: -20 to 70 deg C

• Relative humidity: 5% to 90% non-condensing